



LTDG9333 ARROW LIGHT

Email: export@lhsafe.com
Website: <http://www.lhsafe.com>



FEATURES

Voltage: DC10-30V
Power: 60W
Current: 5A
Frequency: 1-4 Hz
LED QTY: 64 PCS
LED Power: 1W/3W
LED Lifetime: 100000/h
Color: Red Blue White Amber Green Purple
Operating ambient temperature: -30--+70°C
Installation : Screws & bracket
Flash pattern: 27 kinds
Dimension: 987mm L× 370mm W× 60mm H
Weight: 4 KG

WIRING & FUNCTION

RED: (+)DC12-30V
BLACK: Ground (-)
YELLOW: To + VDC For Flash Pattern
BROWN: To + VDC For Flash pattern
BLUE: To + VDC For Right Arrow
ORANGE: To + VDC For Left Arrow
BLUE+ORANGE: To + VDC For Center Out
GREEN: To + VDC For Special Flash
WHITE: To + VDC For Takedown light



Wenzhou Lianheng Safety Equipment Co., Ltd

Tel: 0086-577-88138108
Fax: 0086-577-89896969
Email: export@lhsafe.com Website: <http://www.lhsafe.com>

*All accessories are water, humidity, corrosion and emission resistant, flame retardant, and environmental-friendly. Materials used fully comply with the ROHS regulations.